



SHEATHING OVER
16GA. (1.5mm) (MIN.)
STEEL STUD FRAMING
(BY OTHERS)
SPACED 16" (400mm) O.C. MAX

StoneLite[®] PANEL

FACTORY ATTACHED
INTERLOCKING
CHANNEL

FIELD ATTACH MATING
INTERLOCKING CHANNEL THRU
SHEATHING AND INTO
EACH STUD W/ #10 (5mm)
TEK SCREWS AS REQ'D.

USE BUILDDEX "MAXISEAL"
W/ NEOPRENE WASHER
OR APPROVED EQUAL

AT CONC./CMU WALLS
USE COATED TAP-CONS
W/ NEOPRENE WASHER

2 3/8" (60mm)
MIN. SHIM AS REQ'D.

VAPOR
BARRIER
SHEET
(INSTALLED
BY OTHERS)

SHIM
(BY OTHERS)

WINDLOAD AND
BEARING
APPLICATION

WINDLOAD
APPLICATION

DR-040(10Feb25)

DESCRIPTION:

TYPICAL WIDE INTERLOCKING CHANNEL

SHEET #:
SP-1

SCALE:
NOT TO SCALE

DRAWN BY:
JW

DATE:
3/12/2025



COLDSPRING[®]

17482 GRANITE WEST ROAD, COLD SPRING, MN 56320
PHONE 320.685.3621 | WWW.COLDSPRINGUSA.COM